




PRO RX-14 SERIES

Interactive Flat
Panel Display



	Android 14.0
	RAM 8 GB
	ROM 128 GB


PRODUCT MAY VARY FROM THE ACTUAL PRODUCT



20 Touch Points



5.0 Bluetooth version



Octa-core



Eye protection, lock screen, touch lock and other tools.



20Wx2(INBUILT)

UPTREE INTERACTIVE PANEL

DISPLAY

Active Screen Size	65"	75"	86"
Response time	<4ms	<4ms	<4ms
Aspect ratio	16:9	16:9	16:9
Max Visual Area	1429(H) × 804(V) mm	1651(H) × 929(V) (mm)	1897(H) × 1067(V)mm
Resolution	3840 (H) × 2160 (V)	3840 (H) × 2160 (V)	3840 (H) × 2160 (V)
Pixel pitch	0.372×0.372mm	0.42975 (W) × 0.42975(H)	0.4935×0.4935mm
Frequency	120Hz	120Hz	120Hz
Display Color	1.07B(10bit)	1.07B(10bit)	1.07B (10bit)
Contrast ratio (Typ)	30000:1	30000:1	30000:1
Viewing Angle	178°(H/V)	178°(H/V)	178°(H/V)
Back Light source	DLED	DLED	DLED
Brightness (Typ)	450cd/m2	500cd/m2	600cd/m2
Life span	1,20,000 hours	1,20,000 hours	1,20,000 hours

TOUCH & WRITING

Touch Technology	IR Touch
Supported system	Windows10/Windows8/Windows7/Windows XP/Android/Linux/Mac OS X/Chrome
Touch points	20 points touch
Input mode	Finger, Passive IR pen

SPEAKER

Speaker Max.Power Output	20Wx2(INBUILT)
Soundtrack	2.0

UPTREE CONSULTANCY SERVICES PRIVATE LIMITED

+91 9958600419

info@uptree.in

www.uptree.in

UPTREE INTERACTIVE PANEL

SYSTEM

System version	Android 14.0
Working frequency	1.2GHZ
CPU	8-Core A55
GPU	Octa-core
RAM	8GB
ROM	128GB

BLUETOOTH

Bluetooth version	5.0
Operation frequency	2.4GHZ
Operation distance	0-10m
Remark	Built-in Bluetooth

Wi-Fi

Version	802.11ac/b/g/n/a
Operation frequency	2.4GHz/5GHz
Operation distance	0-10m
Remark	Built-in Wi-Fi mode

FRONT INTERFACE

USB 3.0	3
HDMI IN	1
TOUCH OUT	1
TYPEC	1
Keys	Switch,Home,Screen Down,Record,Touch Lock,Settings

UPTREE CONSULTANCY SERVICES PRIVATE LIMITED

+91 9958600419

info@uptree.in

www.uptree.in

UPTREE INTERACTIVE PANEL

ONBOARD INTERFACE

TF CARD	1
USB 3.0	1
USB 2.0	1
TOUCH	1
HDMI IN	2
HDMI OUT	1
VGA	1
AUDIO IN	1
DP IN	1
RS232	1
RJ45 OUT	1
MIC IN	1
AUDIO OUT	1
COAX	1

POWER PARAMETERS

Voltage	100-240V ~ 50/60Hz	100-240V ~ 50/60Hz	100-240V ~ 50/60Hz
Max power consumption	250W	280W	350W
Standby power consumption	≤0.5W	≤0.5W	≤0.5W

SIZE & WEIGHT

Bare dimension	1484.60×919.88×87.2mm	1706.76×1027.32×87.31mm	1952.96×1167.77×87.18mm
Packing dimension	1630×220×1050mm	1860*220*1160mm	2120*220*1325mm
Net weight	43±1KG	58±1KG	85±1KG
Gross weight	49.5±1KG	68±1KG	98±1KG

UPTREE CONSULTANCY SERVICES PRIVATE LIMITED

+91 9958600419

info@uptree.in

www.uptree.in

UPTREE INTERACTIVE PANEL

ACCESSORIES

Power cord	x1
Stylus pen	x1
Wall mount	x1
Operation manual	x1

ENVIRONMENTAL FACTORS

Working temperature	0°C-40°C
Working humidity	10%-90%RH

UPTREE CONSULTANCY SERVICES PRIVATE LIMITED

+91 9958600419

info@uptree.in

www.uptree.in